

Connect system

- Provides multiple chilled, still & sparkling dispense points all from a single master unit (plus boiling water).
- Removes the need to install individual water systems in serveral location of a building.
- Dispenses water from any number of points to multiple floors as required.
- Boiling water requires compact boiler at each dispense point.
- Continually re-circulates the filtered water to avoid dead legs abd eliminate stagnant water at any point.
- Dispense point options choose from the EauVation range suitable for bottling.
- Increased efficiency against individual units, up to 55% less energy consumption.
- Up to 45% more cost effective than individual units.
- Bespoke installation to ensure optimum flow at all points.



Dispense point options





Acqua 80i/150i

EauVation's Medium & Large Remote water bottling systems are the perfect option for when there is limited space on worktops or counters. These compact systems have been designed to fit perfectly under a bar or counter and supply premium quality, chilled, filtered water (still & sparkling) to a stylish bar tap.



SMARTTAP 2 button

The two touch button SMARTTAP for the home dispenses filtered drinking water with a modular choice of up to 2 functions including boiling, chilled, sparkling and/or ambient. The optional drip-tray lets you install the SMARTTAP in a countertop.. You can do away with the kettle and you'll never need to buy plastic bottled water again, reducing your environmental impact and saving storage space.



SMARTTAP 3 button

SMARTTAP for the home dispenses filtered drinking water with a modular choice of up to 3 functions including boiling, chilled, sparkling and/or ambient. The optional drip-tray lets you install the SMARTTAP in a countertop. Made in England from 316 stainless steel for quality and durability, in either Brushed or Polished finish, the SMARTTAPTM includes built-in safety features.





Master control unit - 280

Cooling capacity (lt/h) 280 Continuous supply (lt) 150 5°-10°C Cold water temperature Ice bank capacity (It) 90 Ice bank (Kg) 35 Cooling technology ICF BANK - double stainless steel coil Condensation forced ventilation (fan) Adjustable thermostat yes natural hydrocarbon gas R - 290 Refrigerant gas 1/2 + hpCompressor power professional carbonator pump Pump

ø 3/8" x 1/4" Inlet water pipe Outlet water pipe ø 8 x 1mm Typology undercounter Supply 220V - 50Hz Power 1265 W -5,5 A Min 5°C - Max 42°C Working room temp Net weight Kg 83 Gross weight Kg 93 Dimensions Lx W x H (mm) 550 x 760 x 720 Packaging dimensions (mm) 600 x 800 x 813 Dispensing chilled and sparkling water



Classeq Ltd, Classeq House, Roebuck Way, Knowlhill Milton Keynes MK5 8WH

Contact: 0844 225 9250 eauvation.co.uk